



CESCA VAULT

Built to Last. Engineered to Protect

 **Cell: (442) 238-6890 & (346) 522-5639**

 **Office: (877) 712-3722**

 **Email: rerdmann@cescausa.com**

 **Email: sales@cescausa.com**

FIBERGLASS AND POLYMER CONCRETE



12X18-T15



AVAILABLE SIZES	
12" x 18" T15	AVAILABLE

AVAILABLE OPTIONS			
			
CUSTOM COLORS Custom colors available to meet project needs.	CUSTOM NAMEPLATES Electric, Telephone, Fiber Optic, Water, Broadband, Traffic, CATV, Communications and more.	SECURE COVER 3/8" stainless steel hex bolt assembly. Optional security bolt upgrade available.	OPEN BOTTOM Allows for easy access, drainage and direct conduit entry.

SPECIFICATION	VALUE
Finish	Natural Color Finish
Floor	No Floor
Cover Rating	T22 / 36K
Bolts	3/8" Hex Bolts
Application	Incidental Traffic – Parking Lot, Sidewalk
Standards / Compliant	WUC 3.6, ASTM C857, ANSI/SCTE 77
Vertical Strength	36,500
Flexural Strength	4,000 PSI
Tested According To	ASTM D-543, ASTM D-570



ISOMETRIC VIEW

TOP VIEW



BABA Certification
Domestic
Manufacturing
Requirements

