



CESCA VAULT

Built to Last. Engineered to Protect



Raul Archundia



Cell: (859) 689-6147



Email: rarchundia@airway.com

FIBERGLASS AND POLYMER CONCRETE

30X48-T15/T22



AVAILABLE SIZES

30" x 48" x 36"

AVAILABLE

AVAILABLE OPTIONS



CUSTOM COLORS

Custom colors available to meet project needs.



CUSTOM NAMEPLATES

Electric, Telephone, Fiber Optic, Water, Broadband, Traffic, CATV, Communications and more.



SECURE COVER

3/8" stainless steel hex bolt assembly. Optional security bolt upgrade available.




OPEN BOTTOM

Allows for easy access, drainage and direct conduit entry.


SPECIFICATION

VALUE

Finish	Natural Color Finish
Floor	No Floor
Cover Rating	T22 / 36K
Bolts	3/8" Hex Bolts
Application	Incidental Traffic – Parking Lot, Sidewalk
Standards / Compliant	WUC 3.6, ASTM C857, ANSI/SCTE 77
Vertical Strength	36,500
Flexural Strength	4,000 PSI
Tested According To	ASTM D-543, ASTM D-570



ISOMETRIC VIEW



TOP VIEW



BABA Certification
Domestic
Manufacturing
Requirements

