



CESCA VAULT


Built to Last. Engineered to Protect

☎ Cell: (442) 238-6890 & (346) 522-5639
☎ Office: (877) 712-3722
✉ Email: rerdmann@cescausa.com
✉ Email: sales@cescausa.com

POLYMER CONCRETE
36X60-T22





AVAILABLE SIZES	
36" × 60" × 24"	AVAILABLE
36" × 60" × 30"	AVAILABLE
36" × 60" × 36"	AVAILABLE
36" × 60" × 48"	AVAILABLE

AVAILABLE OPTIONS			
 CUSTOM COLORS Custom colors available to meet project needs.	 CUSTOM NAMEPLATES Electric, Telephone, Fiber Optic, Water, Broadband, Traffic, CATV, Communications and more.	 SECURE COVER 3/8" stainless steel hex bolt assembly. Optional security bolt upgrade available.	 OPEN BOTTOM Allows for easy access, drainage and direct conduit entry.

SPECIFICATION	VALUE
Finish	Natural Color Finish
Floor	No Floor
Cover Rating	T22 / 36K
Bolts	3/8" Hex Bolts
Application	Incidental Traffic – Parking Lot, Sidewalk
Standards / Compliant	WUC 3.6, ASTM C857, ANSI/SCTE 77
Compressive Strength	11,500 PSI
Flexural Strength	4,000 PSI
Tested According To	ASTM D-543, ASTM D-570

TOP VIEW



ISOMETRIC VIEW



BABA Certification
Domestic
Manufacturing
Requirements

